

LiFePO4 BATTERY



KEY FEATURE



Safety

Self-developed LFP Battery
Safely proved by thousands of electric vehicles



Reliability

LFP R&D started from 2016
1,000+ systems in 10+ countries




High Usable Capacity

90% usable capacity



Easy Installation

Pre-wired cabinet
3U format modular battery



Perfect Compatibility

Compatible with leading single
& three-phase inverter

LiFePO4 BATTERY



1 X JOLTA BATTERY



OR



4 X JOLTA BATTERY



16 X JOLTA BATTERY



TECHNICAL PARAMETERS **LiFePO₄** BATTERY

JB5110240N - 51.2V

PERFORMANCE

Voltage (Nominal)	51.2 V
Maximum Charge Voltage	57.6 V
Discharge Cut-Off Voltage	46 V (Configurable)
Total Energy	10.24kWh
Total Current	200Ah
Continuous Discharge Current	200A
Continuous Charge Current	100A
Cut off Current	10 A
ESR/AC @ 1KHZ	< 10 mΩ

PHYSICAL SPECIFICATION

Weight	84 kg (Module) 87 Kg (With Pack)
Module Casing Material	MS/Aluminum
Terminal Type	M10
Dimensions (L x W x H)	736 x 330.2 x 252 mm
Dimensions (L x W x H) pack.	901.7x 381 x 317.5 mm

FEATURES

Alarm	Alarm for under/Over Voltage-Over Current, Out of Range Temperature
-------	---

COMPATIBLE INVERTERS (All Inverters)



SERVICE LIFE

Projected Calendar Life ³	≥ 10 years
Shelf Life	5 Years

SAFETY PERFORMANCE ENVIRONMENT

Over/under voltage	Unit shut down
Over Current	Unit shut down
Over Temperature	Unit shut down
Cell Operating Temperature ³	-10°C to 60°C
Operating Humidity	Non-Condensing

ADDITIONAL

Parallel Connection	YES
Series Connection	Custom Option
Self-Discharge	2-3% month
Recommended Discharge Depth	80%



[1] DC Usable Energy, test conditions: 100% DOD, 0.2C charge & discharge at +25°C. System Usable Energy may vary due to system configuration parameters.

[2] Charge derating will occur between 0°C and +15°C.